

Optional Features

Auxiliary Hydraulic Valve Kit - Allows operator to use quick connect to power an auxiliary hydraulic implement.

Bio Oil - Tired of paying for customer driveways? Donkey offers a water based biodegradable hydraulic fluid (not recommended on 3WD units)

Block Heater - 110 V plug in engine block heater

Custom Color - Send us your paint specifications, and we will paint a sample plate and send it back for approval. Once approved, a Donkey will be painted to match your fleet.

Donkey Horn - In place of a standard horn, we offer a DONKEY horn. This simulates the sound of a donkey braying and is great for attention getting!

Donkey Glide - An accumulator is tied in with the mast hydraulics. The accumulator is pressured with nitrogen and absorbs shock from the load.

Dual Rear Axle - This feature is unique to the Donkey and is utilized for roll laying of sod. A rotary sod layer is usually purchased with this model.

Extension Step - Lowers to allow the driver a safer entry and exit when the lift is truck mounted.



Block Heater



Donkey Glide



Extension Step



Custom Color



Dual Rear Axle



Optional Features, Cont'd

Lumber Guard - These moveable aluminum guards protect long product and can be easily positioned to prevent interference during mounting.

Fork Positioner - This feature allows the operator to hydraulically adjust the fork spacing from the comfort of the driver's seat.

Heavy duty tilt cylinders and rod ends - These are standard on the 5K and 4KCH and extended reach, but are available as an option on other models.

High capacity pump - This option increases the volume of hydraulic output from 11 GPM to 15.8 GPM at 3,000 RPM. Only available on 4 cylinder engines.

Couter Weight - The 5K comes standard with 150 lb. and the 4KCH comes standard with 100lb of counterweight. It is available on other models in either 100 or 150 lb. options.

Remote Valve - This feature is an excellent addition to the safety conscious employer. The Donkey can be mounted and unmounted without the driver climbing on or off the unit. The driver can operate the mounting controls while standing safely on the ground.

Sun shade - An AL sunshade is mounted to the top of the operator compartment.



Lumber Guard



Fork positioner in use



High Capacity Pump



Counter Weight



Remote Valve



Sun Shade